

DuraPak

Calibrated Polyester Press UnderPacking

DuraPak

CHARACTERISTICS/ADVANTAGES



Adhesive Formulation ~ *Holds Permanently to the cylinder*
 Functionality ~ *Suitable for Auto-Plate hanging systems*
 Gauge Stamped ~ *Indicates how cylinders are packed*
 Broad Caliper Range; 0.05 mm – 0.55 mm ~ *Flexibility in packing*
 High-Density ~ *Maintains gauge during the run, sharper dots*
 Uniform Gauge Profile ~ *Yields uniform solids and quality output*
 Narrow Tolerances ~ *Consistent & Dependable performance*
 - *Durable*

UTILITY

Suitable for use under

✓ **Plates Only**

✗ Blankets ~ Printing Unit or Coating Unit (Creates excessive vibration and may cause streaking)

✗ Back Cylinder

APPLICATIONS / PROCESS

● Sheetfed (plate only) ● Heatset /Coldset Web (plate only)
 ● Commercial Printing ● Label /Forms ● Newspaper ● Packaging

SPECIAL FEATURES

Adhesive Coated

Adheres to cylinder permanently

TECHNICAL DATA

Construction	100% Pure Polyester
Type	Full Adhesive Backing, Non-Compressible
Surface Finish	Steel Calendared
Colour	Clear to Milky
Nominal Thickness	Target +/- 5%
Surfaces	Plastic Film (moisture resistant)

AVAILABILITY

General Gauges (")

Sheets and Rolls; Max sheet size 49" x 82"
 .003", .004", .005", .006", .007", .008", .009"
 .010", .011", .012", .016", .018", .020", .022"