


LithPak

High Performance Calibrated Press Under-Packing

PRODUCT FEATURES / BENEFITS



- Anti-Corrosion Treated ~ Prevents rusting and damage to presses
- Anti-Creep Formulation ~ Resists slipping movement
- Anti-Wicking Treatment ~ Resists moisture at edges, longer lasting
- Key Gauge Range ~ Pack most any press, Every sheet gauge stencilled
- High-Density ~ Maintains gauge during the run, sharper dots
- Excellent Formation ~ Yields uniform solids and quality output
- Contains Recycled Fibres ~ Environmentally Friendly Formulation

UTILITY

Suitable for use under

- ✓ Plates
- ✓ Blankets ~ Printing Unit or Coating Unit
- ✓ Back Cylinder

APPLICATIONS / PROCESS

- Sheetfed
- Heatset Web
- Coldset Web
- Commercial Printing
- Label /Forms
- Newspaper
- Packaging

TECHNICAL DATA

Construction	Treated Virgin and Recycled Cellulose Fibers
Type	Non-Adhesive, Non-Compressible
Surface Finish	Steel Calendered
Color	Ivory
Nominal Thickness	Target +/- 3% (Industry Spec +/- 5%)
Surfaces	X,Y Axis; Sized (moisture resistant) Z Axis; Sized (wicking resistance)

AVAILABILITY

General	Sheets and Rolls; Max sheet size 63" x 84"
Gauges (mm)	.002" - .016"