


ParaTex

Precision Engineered Calibrated Press Under-Packing



CHARACTERISTICS/ADVANTAGES



Latex Saturated

- ~ Absorbs Press Vibrations-Eliminates streaking and marking
- ~ Resists moisture, longer lasting (up to 30 million Impressions)

Open Cell Structure

- ~ Excellent compression & full rebound-Extends blanket life
- ~ Evens out blanket irregularities-eliminates distortion

Broad Caliper Range; .016" - .051" ~ Flexibility in packing

Narrow Tolerances ~ Consistent & Dependable performance

UTILITY

Suitable for use under

✗ Plates

✓ Blankets ~ Printing Unit, Excellent for Coating Units

✓ Back Cylinder

APPLICATIONS / PROCESS

- Sheetfed
- Heatset Web
- Coldset Web
- Commercial Printing
- Label /Forms
- Newspaper
- Packaging

SPECIAL FEATURES

Latex Saturated ParaTex

Absorbs Press
Vibrations (3 axis)
Eliminates streaks &
marking



Vibration Absorption
Precise Dot Structure



Vibrations Cause
Dot Structure Problems



TECHNICAL DATA

Construction

Latex Impregnated Cellulose, Nonwoven
and Synthetic Fibers

Type

Open Cell Compressible

Surface Finish

Calendared

Surface Smoothness

200 – 280 TAPPI Sheffield

Colour

Orange

Nominal Thickness

Target +/- 0.005"

AVAILABILITY

General

Sheets Only;

Non-Adhesive Gauges

.016", .020", .024", .026", .028", .030", .032, .036", .038", .040", .051"
Maximum sheet size 34" x 44"