

PolyPak

Calibrated Polyester Press UnderPacking

PolyPak

CHARACTERISTICS/ADVANTAGES



NON-Adhesive Formulation ~ *Spray Mount to the cylinder*
 Functionality ~ *Suitable for Auto-Plate hanging systems*
 Gauge Stamped ~ *Indicates how cylinders are packed*
 Broad Caliper Range; .002" – .014" ~ *Flexibility in packing*
 High-Density ~ *Maintains gauge during the run, sharper dots*
 Uniform Gauge Profile ~ *Yields uniform solids and quality output*
 Narrow Tolerances ~ *Consistent & Dependable performance*
 - *Durable*

UTILITY

Suitable for use under

✓ **Plates Only**

✗ Blankets ~ Printing Unit or Coating Unit (Creates excessive vibration and may cause streaking)

✗ Back Cylinder

APPLICATIONS / PROCESS

● Sheetfed (plate only) ● Heatset /Coldset Web (plate only)
 ● Commercial Printing ● Label /Forms ● Newspaper ● Packaging

SPECIAL FEATURES

NON-Adhesive Coated

Adheres with Spray-Mount Adhesive to cylinder permanently

TECHNICAL DATA

Construction

100% Pure Polyester

Type

Non Adhesive Backing, Non-Compressible

Surface Finish

Steel Calendared

Colour

Clear to Milky

Nominal Thickness

Target +/- 5%

Surfaces

Plastic Film (moisture resistant)

AVAILABILITY

General

Sheets and Rolls; Max sheet size 49" x 82"

Gauges (")

.002", .003", .004", .005", .006", .008", .010"
 .012", .014"